

Wipers

Profile	Type
	WR01
	WR01A
	WR02
	WR02A
	WR02B
	WR02C
	WR02D
	WR03
	WR04
	WR07
	WR08
	WR11
	WR12
	WR13
	WR13_E2
	WR14
	WR15
	WR17
	WR18

Rod seals

Profile	Type
	RS01
	RS01A
	RS01B
	RS02
	RS02A
	RS02B
	RS03
	RS04
	RS05
	RS08
	RS09
	RS09A
	RS09B
	RS91
	RS91B
	RS16
	RS17
	RS17A
	RS17B
	RS17C
	RS17D
	RS17E
	RS19
	RS20
	RS31-33
	RS35

Piston seals

Profile	Type
	PS01
	PS01A
	PS01B
	PS02
	PS02A
	PS03
	PS04
	PS05
	PS08
	PS08A
	PS08B
	PS08C
	PS08D
	PS08E
	PS08F
	PS09
	PS09A
	PS16
	PS16A
	PS17
	PS17A
	PS17B
	PS19
	PS20
	PS23
	PS35

Symmetrical seals

Profile	Type
	PRS06
	PRS06A
	PRS06B
	PRS06C
	PRS06D
	PRS06E
	PRS07
	PRS10SP
	PRS10-12
	PRS13-15
	PRS18
	PRS19B
	PRS19C
	PRS19D
	PRS22
	PRS99

Static seals and O-rings

Profile	Type
	FL01A
	FL02B
	FL03
	OR
	ORH
	ORV
	QR01
	SS01

Back-up rings

Profile	Type
	BUR08
	BUR09
	BUR10
	BUR11
	BUR12
	BUR13

Guide rings

Profile	Type
	BWR01
	BWR01A
	BWR03
	BWR04
	BWR05
	BWR06
	BWR07
	BWR08
	BWR09

Customized seals

Profile	Profile

Rotary seals

Profile	Type
	OS01
	OS02
	OS08
	R03
	R04
	R04A
	R05
	R05A
	VR06
	VR07
	R08
	R08D
	R09
	R09A
	R10
	R10A
	R11
	RS19A
	PS19A

Mining seals

Profile	Type
	P50
	P50A
	P51
	P51A
	P51G
	P52
	P53
	P54
	P54A
	P55
	R50
	R50A
	R51
	R52
	R53
	W50
	W51
	W53
	W54
	BWR01-P
	BWR01-R
	P58

Table of materials

	Description	Color	Application temp.	Hardn. at 20°C
POLYURETHANE	PU Red AF1009 U500-R95		-30 to +125°C	Shore A 95 +/-2
	PU Red AF1001 U203-R95		-30 to +105°C	Shore A 95 +/-2
	PU Green AF1002 U203-G95		-30 to +105°C	Shore A 95 +/-2
	PU FDA Light Blue AF1003 U203-B95		-30 to +105°C	Shore A 95 +/-2
	PU FDA Natural AF1006 U203-95FDA		-30 to +100°C	Shore A 95 +/-2
	PU MoS <sub>2</sub> Grey AF1005 U203-GM95		-30 to +105°C	Shore A 95 +/-2
	PU LT Dark Blue AF1004 U203-B95-LT		-50 to +105°C	Shore A 95 +/-2
	PU 57 Shore D Dark Blue AF1007 U203-D57		-30 to +90°C	Shore D 57 +/-2
	PU 57 Shore D + MoS <sub>2</sub> Grey AF1008 U203-D57G		-30 to +90°C	Shore D 57 +/-2
	NBR	NBR Black AF1201 N107-B85		-25 to +100°C
NBR 95 Black AF1202 10N109-B95			-25 to +100°C	Shore A 95 +/-5
NBR FDA White AF1203 N111-W85			-22 to +100°C	Shore A 85 +/-3
H-NBR	H-NBR Black AF1301 HN112-B85		-25 to +150°C	Shore A 85 +/-5
	H-NBR RGD Black AF1302 HN900-B85-RGD		-20 to +150°C	Shore A 85 +/-5
	H-NBR RGD LT Black AF1303 HN901-B85-RGD		-35 to +150°C	Shore A 85 +/-5
FPM	FPM Brown AF1601 F109-BR85		-20 to +210°C	Shore A 85 +/-5
	FPM FDA Brown AF1602 F110-BR85		-20 to +210°C	Shore A 85 +/-5
	FPM Black AF1603 F111-B85		-25 to +210°C	Shore A 85 +/-5
	FPM-RGD Black AF1604 F800-B85-RGD		-30 to +200°C	Shore A 85 +/-5
	EPDM Black AF1401 E131-B85		-50 to +130°C	Shore A 85 +/-5
EPDM	EPDM FDA White AF1402 E132-W85		-50 to +100°C	Shore A 85 +/-3
	EPDM KTW Black AF1403 E133-W270		-40 to +120°C	Shore A 85 +/-5
	SILICONE	Silicone FDA Red AF1701 S102-R85		-55 to +210°C
Silicone FDA Blue AF1702 S103-BL85			-55 to +180°C	Shore A 85 +/-3
AFLAS Black AF1501 AF101-B85			-15 to +210°C	Shore A 85 +/-5
PTFE	PTFE-F Frey AF106 T105-G		-200 to +260°C	Shore D 55 - 64
	PTFE-P FDA Ewhite AF001 T101-W		-200 to +260°C	Shore D 51 - 60
	PTFE-40% Bronze Brown AF402 T110-BR40		-200 to +260°C	Shore D 62 - 67
	PTFE-40% Bronze Blue AF410 T115-BR40		-200 to +260°C	Shore D 62 - 67
	PTFE-60% Bronze Brown AF401 T120-BR60		-200 to +260°C	Shore D 65 - 70
	PTFE-25% Carbon Grey AF201 T125-C25		-200 to +260°C	Shore D 62 - 67
PLAST	POM FDA White AF907 P101-WE		-60 to +100°C	-
	PA FDA Natural A112-WC		-30 to +105°C	-
	PEEK Natural Beige AF807 PK100-CN		-50 to +250°C	Shore D 90
	UHMW - PE White AF707 PE1000-HD		-200 to +80°C	Shore D 60 - 65

In addition to our standard profiles we can now also supply special profiles and engineered plastic products according to customer drawings or specific demands

The indicated minimum application temperatures are thought as a general guideline, because a seal's function at low temperatures is dependent on the kind of the seal, the general application conditions, and on the kind of the surrounding metal parts the seal is in touch with. The indicated upper temperature limits may be exceeded, but this reduces the service life. Other materials available on request.

In case of doubt you are always welcome to contact our application engineers.