

AF907 ACETAL Copolymer Data Sheet

Polyoxymethylene (Acetal) is a semi-crystalline thermoplastic engineering material with high strength and rigidity, excellent machinability and suitable for many varied applications.

- Very good electrical insulation
- Resistant to dilute acids and most solvents
- Good sliding properties
- Strong and rigid
- Easily welded
- Easily machined

Typical Physical properties

Property	Test Method	Value
Density	ASTM D792	1.41 g/cm ³
Tensile (At yield) 23°C	ASTM D638	60 MPa
Elongation (At break) 23°C	ASTM D638	30%
Max service temperature		140°C
Specific volume resistance	DIN 60093	10 ¹⁴ Ω CM
Dielectric strength 1mm	ASTM 149	>50

Issued October 2009. ©AFT Technical Department.

Images are for illustrative purposes only. Please contact AFT for alternative or specific designs. This does not represent a legally binding guarantee of certain properties or the suitability for specific applications. All information is provided in good faith at time of print.

AFT Fluorotec

Solutions and components in Fluoropolymer Plastics

Phone: +44 (0) 1992 515880
Fax: +44 (0) 1992 554490
Email: info@fluorotec.com
Website: www.fluorotec.com

Unit 2, Pages Old Mill
 Tamworth Road
 Hertford
 Herts. SG13 7DG