

AFC 2301

AFC 2301 is a high build coating for extreme duty applications. A High purity Fluoropolymer coating based on a unique alternating copolymer, which offers excellent coatability, hardness, abrasion and chemical resistance. Ideal for applications within Pharmaceutical, Food, Fine chemicals and semi conductor process plant where high purity and low gas permeation is required.

- Optimum permeation resistance
- Excellent hardness, abrasion and chemical resistance
- High Purity
- Very Good surface characteristics
- Excellent chemical resistance
- Non Flammable
- Non Conductive
- Black or Green in colour

Typical Physical properties

Property	Value
Thickness	0.2 – 1.00mm
Hardness Shore D	80
Operating Temperature range °C	-50°C to +160°C
Tensile Strength	7500 PSI
Water Absorption	<0.02%
Useable pH Range	1 – 14
Specific Gravity	1.75

Issued March 2015 AFT Fluorotec Technical Department

All information is based on typical test results performed under specific conditions and limited sample size. This does not represent a legally binding guarantee of certain properties or the suitability for specific applications. All information is provided in good faith at time of print.

AFT Fluorotec Coatings Ltd
Fluoropolymer Coating Solutions

Phone: +44 (0) 1992 515880
Fax: +44 (0) 1992 554490
Email: coatings@fluorotec.com
Website: www.fluorotec.com

